

Product : ONYX
GSM Range – 250 – 450 g/m² WHITE BACK

Parameters	GSM-250 ± 3%	GSM-285 ± 3%	GSM-300 ± 3%	GSM-320 ± 3%	GSM-350 ± 3%	GSM-400 ± 3%	GSM-450 ± 3%
Brightness on Top (± 1%)	78	78	78	78	78	78	78
Brightness on Bottom (± 1%)	71	71	71	71	71	71	71
Caliper Microns (± 5%)	292	333	351	377	413	476	535
Bulk cc/gm (± 5%)	1.17	1.17	1.17	1.18	1.18	1.19	1.19
Stiffness							
MD Taber (± 10%)	75	90	110	130	150	230	280
CD Taber (± 10%)	35	45	55	65	75	105	130
Gloss %	45-50	45-50	45-50	45-50	45-50	45-50	45-50
Cobb Top g/m2	40-45	40-45	40-45	40-45	40-45	40-45	40-45
Cobb Bottom g/m2	45-50	45-50	45-50	45-50	45-50	45-50	45-50
Moisture	6.0-7.0	6.0-7.0	6.0-7.0	6.0-7.0	6.5-8.0	6.5-8.0	7.0-8.0
Wax Pick	7A	7A	7A	7A	7A	7A	7A